

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS


IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47G 9/00	A1	(11) International Publication Number: WO 97/43933 (43) International Publication Date: 27 November 1997 (27.11.97)
(21) International Application Number: PCT/DK97/00234 (22) International Filing Date: 22 May 1997 (22.05.97) (30) Priority Data: 9600179 23 May 1996 (23.05.96) DK (71) Applicant (for all designated States except US): DANESTYLE LEISURE ACCESSORIES A/S [DK/DK]; Valhøjs Allé 190, DK-2610 Rødovre (DK). (72) Inventor; and (75) Inventor/Applicant (for US only): NOLDUS-NILSEN, Morten [NO/DK]; Bel Colles Allé 8A, DK-2960 Rungsted Kyst (DK). (74) Agent: HEIDEN & HØIBERG A/S; Nørre Farimagsgade 37, DK-1364 København K (DK).		(81) Designated States: AU, BY, CA, CN, JP, KR, NO, RU, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: SUPPORTING ARTICLE (57) Abstract A supporting article (1; 12) for com- forting support of body parts and made of at least two layers (2; 15) of web material welded together, which defines at least one compartment. The at least one compartment is made as an air channel (3; 14) extending by a greater part of the periphery (4; 15) of the article and is closed by a valve means (5; 16). Furthermore, the air channel de- fines a central area (6; 17) of intermediary material. Hereby, a particular comforting support is achieved, which secures a stable positioning of the head or parts of a body.		



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SUPPORTING ARTICLE

5 The novel invention relates to a supporting article for comforting support of one or more parts of a body and which is made of at least two layers of material welded together, which defines at least one compartment.

Supporting articles for support of parts of a body are known, such as support of the head in a resting position or the body in a lying position.

10 These known supporting articles are also either provided with many separate discrete air chambers or just one chamber which has a substantially similar cross section area along its entire extension.

15 The known supporting articles often involve an unsatisfactory support without the desired high comfort.

20 The supporting article for the comforting support of parts of a body according to the present invention is characterised in that the at least one compartment is made as an air channel extending by a greater part of the periphery of the article and is closed by a valve means and also defines a central area of intermediary material.

By this, an especially comforting support is provided which ensures a stable positioning of the head or supported parts of a body.

25 In the present context, the term "a greater part of the periphery" means that the channel extends by more than 50 % of the periphery of the supporting article when the air channel is empty, and may extend up to 99,9 % of the periphery whereby the two ends of the air channel almost meet.

30 The supporting article may be of various geometric shapes in plan view, e.g. as may be seen in Fig. 1 and Fig. 4. When the supporting article has four more or less well-defined sides, the air channel will typically extend along approximately 3 of the 4 sides of the supporting article, such as from 55 % to 90 % of the periphery.

Depending on the shape of the articles the air channel may extend from 60 to 80 %, such as 65 to 75 %.

- 5 An especially good and secure support is obtained when the air channel extending by a greater part of the periphery of the article is designed with different cross sections along the periphery of the article.

- 10 It has proved especially appropriate that the cross section area of the said air channel is smallest in parts where the channel alters direction thereby providing the supporting article with especially stable edge areas in between the alteration of direction of the channel.

- 15 According to the invention the extensions of the air channel on opposite sides of the central area may be designed with similar cross section forms.

By this, the best possible support of a head in a resting position is provided as well as a particular good positioning of parts of the body within the central area.

- 20 Especially, a particular good support for the head is obtained when the rest of the air channel connecting the parts of the air channel at the opposite sides of the central area having the similar cross section forms, is designed with a substantially smaller cross section area than at the said similar cross section areas.

- 25 The ratio of this substantially smaller cross section area to the similar cross section areas may be from 1:100 to 1:1, such as from 1:50 or 1:20 to 1:2, more preferably from 1:10 to 1:3.

- 30 The ratios of the parts where the channel alters direction to the rest of the channel may be from 1:100 to 1:1, preferably from 1:50 to 1:1, more preferably from 1:20 to 1:1.

According to the invention, the central area may further comprise a compartment.

Furthermore, the compartment of the central area may be filled with resilient material, preferably foam material, so that the support as well as the comfort is most satisfactory.

5

By a particularly appropriate embodiment of the invention the resilient material in the compartment in the central area may be in a compressed state, and the web material defining said central compartment may be provided with an opening which is sealed with a fixed cover.

10

When the novel support is going to be used all that has to be done is removing the cover, such that the opening is exposed, and the air may enter into the foam material via the opening during expansion of the foam material. The cover over the opening is preferably adhesive.

15

Finally, it must be said that the compartment of the central area may also be constructed as an air chamber provided with a valve means.

20

The web material used in the present invention may be any kind of material, such as plastic material, suitable for being welded by heat-bonding, ultra sound and/or high frequency welding. The web material is furthermore suitable as walls in air chambers, i.e. the material is substantially or totally airtight.

25

The invention is explained in detail below referring to the especially preferred embodiments and the drawings and the photo, wherein:

Fig. 1 shows a supporting article for support of parts of a body

30

Fig. 2-3 show section A-A and B-B, respectively, through the supporting article shown in Fig. 1.

Fig. 4 shows a supporting article for support of the head.

Fig. 5-6 show section A-A and B-B, respectively, through the supporting article shown in fig. 4.

Fig. 7 shows in perspective view a supporting article for support of the head.

5

Fig. 8 A is a plan view in perspective of a supporting article for support of parts of a body or in case of a baby, a whole body.

Fig. 8 B is a end view of the article of Fig. 8 A.

10

Fig. 8 C is an side view of the article of Fig. 8 A.

Fig. 9 A is a plan view in perspective of a supporting article for support of the head.

15

Fig. 9 B is a side view of the article of Fig. 9 A.

Fig. 9 C is an end view of the article of Fig. 9 A.

20

In Fig. 1 the shown supporting article 1 for support of parts of a body according to the present invention is made of at least two layers 2, of web material welded together, and comprises an air channel 3 extending by a greater part of the periphery 4 of the article and is closed by a valve means 5 and also defines a central area 6 of intermediary material.

25

Preferably, the valve means 5 is of a known type for blowing in air and subsequent closing. Such as is known from air beds and beach balls.

30

The air channel 3 has the smallest cross section area in parts, where the channel alters its direction 7, whereby the supporting article is given particularly stable edge areas in between the alterations of direction of the channel.

At its extensions at opposite sides of the central area 6, the air channel 3 is designed with similar cross section forms 8.

In a first embodiment shown in Fig. 1-3, the central area 6 comprises a compartment 9.

5 The compartment 9 is filled with resilient material, preferably foam material.

In a particularly appropriate embodiment according to the invention the resilient material in the compartment 9 of central area 6 may be in the compressed state, and the web material defining said central compartment 9 may be provided with an
10 opening 10, which is sealed with a fixed cover 11.

When the novel supporting article 1 is to be used the cover 11 is simply removed so that the opening 10 is exposed and the air may enter into the foam material via the opening 10 during expansion of the foam material. The cover 11 is preferably ad-
15 hered over the opening 10.

Finally, the compartment 9 of the central area 6 may also be an air chamber provided with a traditional known valve means.

20 According to another embodiment shown in Fig. 4-7 the supporting article 12 for support of the head is made of at least to layers 13 of web material welded together, and comprising an air channel 14 extending by a greater part of the periphery 15 of the article and is closed by a valve means 16 and also defines a central area 17 of intermediary material.

25 The air channel 14 has the smallest cross section area in parts, where the channel alters its direction 18, whereby the supporting article is given particular stable edge areas in between the alterations of direction of the channel. In these edge areas, a projecting flap of material welded together is often left, which is a further stabiliser.

30 According to the invention at its extensions on opposite sides of the central area 17, the air channel 14 is designed with similar cross section forms 19. Hereby the best possible support for the head is provided.

A particular good support for the head is achieved when the rest of the air channel 14 connecting the extensions of the air channel at the opposite sides of the central area 17 having the similar cross section forms 19 is made with a substantially smaller cross section area 20 than said similar cross section forms 19.

10

The air channel 14 extending by a greater part of the periphery of the article 15 is made with different cross section areas 19; 20 at the extension along the periphery 15 of the article.

CLAIMS:




1. A supporting article (1; 12) for comforting support of body parts and made of at least two layers (2; 15) of web material welded together, which defines at least one compartment, and wherein the at least one compartment is made as an air channel (3; 14) extending by a greater part of the periphery (4; 15) of the article and is closed by a valve means (5; 16) and also defines a central area (6; 17) of intermediary material.
2. A supporting article according to claim 1, wherein the air channel (14) extending by a greater part of the periphery of the article 15 is made with different cross section areas (19; 20) at its extension along the periphery (15) of the article.
3. A supporting article (1; 12) according to claim 2, wherein the air channel (3; 14) has the smallest cross section area in parts, where the channel alters its direction (7; 18).
4. A supporting article (1; 12) according to claim 1, wherein the air channel at its extensions on opposite sides of the central area (6; 17) comprises similar cross section forms (8; 19).
5. A supporting article (12) according to claim 4, wherein the rest of the air channel (14) connecting the extension of the air channel at the opposite sides of the central area (17) with the similar cross section forms (19), is made with a substantially smaller cross section area (20) than the said similar cross section areas (19).
6. A supporting article (1) according to claim 1, wherein the central area (6) comprises a compartment (9).
7. A supporting article (1) according to claim 6, wherein the compartment (9) of the central area (6) is filled with resilient material, preferably foam material.




8. A supporting article (1) according to claim 7, wherein the resilient material in the compartment (9) of the central area (6) is in compressed state, and the web material defining said central compartment (9) is provided with an opening (19), which is sealed with a fixed cover (11).

5

9. A supporting article (1) according to claim 6, wherein the compartment (9) of the central area (6) is made as an air chamber provided with a valve means.

1/7





3/7




Fig. 7

4/7




Fig. 8A

5/7




Fig. 8B




Fig. 8C

6/7




Fig. 9A

7/7




Fig. 9B




Fig. 9C

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 97/00234

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A47G 9/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A47G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4181990 A (P.J.SANTO), 8 January 1980 (08.01.80), figures 1,3, abstract --	1-9
Y	EP 0094985 A1 (MADSEN,HENNING), 30 November 1983 (30.11.83), figures 1,3, abstract --	1-9
Y	DE 2430213 A (ERICH FREUND), 15 January 1976 (15.01.76), figures 1-2, claims 1-2 --	1-9
A	FR 766794 A (M.FRANK MITCHELL ET AL), 4 July 1934 (04.07.34), figures 1,2, claims 1,2 -- -----	1-9

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

8 October 1997

21 -10- 1997

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Agneta Änggård

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

01/09/97

International application No.
PCT/DK 97/00234

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	4181990	A	08/01/80	NONE	
EP	0094985	A1	30/11/83	NONE	
DE	2430213	A	15/01/76	NONE	
FR	766794	A	04/07/34	NONE	